



CODE	A	B	C	D	E
M44020200	1/4"	8	43.5	33.4	82
M44030300	3/8"	8	43.5	33.4	82
M44040400	1/2"	10	47	40.7	86
M44060600	3/4"	14.5	50	43.3	86
M44080800	1"	19	57.8	50.3	114.5
M44101000	1 1/4"	24	65.2	55	114.5
M44121200	1 1/2"	30	81	65.7	127
M44161600	2"	37	95	75	157

M44020200	LEVER BALL VALVE FF 1/4"
M44030300	LEVER BALL VALVE FF 3/8"
M44040400	LEVER BALL VALVE FF 1/2"
M44060600	LEVER BALL VALVE FF 3/4"
M44080800	LEVER BALL VALVE FF 1"
M44101000	LEVER BALL VALVE FF 1 1/4"
M44121200	LEVER BALL VALVE FF 1 1/2"
M44161600	LEVER BALL VALVE FF 2"

**Specification**

Fields of applications: water  
 Maximum working pressure: 16bar  
 Maximum working temperature: 110°C

9				1	
8		Lock Nut	SS304	1	
7		Handle	Q235+PVC	1	
6		o-ring	EPDM	2	
5		Spindle	HPb59-T	1	
4		Seat	PTFE	2	
3		Ball	HPb59-T	1	CP
2		Bonnet	CW617N(企)	1	NP
1		Body	CW617N(企)	1	NP
NO.	parts NO.	parts name	material	QTY.	note

			<i>Title</i>		Projection	Scale	Size
			MF Lever Ball Valve F x F			1:1	A4
					Material:		Weight
							×g
Mrk		Modification	Date				
Drawn :		Alger.li		NO. :		Sheet	
Checked:				Client NO. :		1/1	
Appr. :						REV.	
Tolerances unless otherwise specified: ISO 2768-mk				<b>IDC BEIJING</b>		01	