



| | | | | | |
|-----|------------------------|----------|--------|----------------|--|
| 8 | | | | | |
| 7 | Washer | EPDM | 1 | | |
| 6 | Brass core | CW617N | 1 | | |
| 5 | Flat nut | Brass | 1 | Nickel plating | |
| 4 | Stainless steel sleeve | SS304 | 2 | | |
| 3 | Isolating Valve | CW617N | 1 | Nickel plating | |
| 2 | Olive | H65 | 1 | | |
| 1 | Compersion Nut | Brass | 1 | Nickel plating | |
| NO. | parts NO. | material | number | note | |

| | | | | |
|--|--|-----------------|--------|------|
| Title | | | Scale | Size |
| 15Cx1/2F-x50CM Flex Tap Con cw Iso - WRAS | | | | |
| Material: | | | Weight | |
| NO.: | | | Sheet | |
| Drawn: | | NO.: | | 1/1 |
| Checked: | | Client NO.: | | REV. |
| Appr.: | | MFLXCTC1510450V | | 01 |
| Tolerances unless otherwise specified: ISO 2768-mk | | BEIJING | | |

Specification
 Fields of applications: water
 Maximum working pressure: 1.0MPa
 Working temperature: 0-85°C

1 2 3 4 5 6