



Specification  
 Fields of applications: water  
 Maximum working pressure: 1.0MPa  
 Working temperature: 0-85°C

| NO. | parts NO. | parts name             | material | number | note           |
|-----|-----------|------------------------|----------|--------|----------------|
| 8   |           |                        |          |        |                |
| 7   |           | Washer                 | EPDM     | 1      |                |
| 6   |           | Brass core             | CW617N   | 1      |                |
| 5   |           | Flat nut               | Brass    | 1      | Nickel plating |
| 4   |           | Stainless steel sleeve | SS304    | 2      |                |
| 3   |           | Male thread adapter    | CW617N   | 1      | Nickel plating |
| 2   |           | Olive                  | H65      | 1      |                |
| 1   |           | Compersion Nut         | Brass    | 1      | Nickel plating |

|   |              |                              |  |
|---|--------------|------------------------------|--|
| Title   |              | 22Cx3/4Fx30CM Flex Tap Con - |  |
| WRAS  |              |                              |  |
| Mark  | Modification | Date                         |  |
| Drawn:  |              |                              |  |
| Checked:  |              |                              |  |
| Appr.:  |              |                              |  |
| Tolerances unless otherwise specified:<br>ISO 2768-mK |              |                              |  |

**IDB BEIJING** Client NO.: MFLEXTC220630

|      |            |       |          |
|------|------------|-------|----------|
| NO.: | Projection | Scale | Size     |
|      | Material:  | 1:1   | A4       |
|      |            |       | Weight   |
|      |            |       | Sheet    |
|      |            |       | REV. 1/1 |
|      |            |       | 01       |