



Specification
 Fields of applications: water
 Maximum working pressure: 1.0MPa
 Working temperature: 0-85°C

| NO. | parts NO. | parts name | material | number | note |
|-----|-----------|------------------------|----------|--------|----------------|
| 8 | | | | | |
| 7 | | Washer | EPDM | 1 | |
| 6 | | Brass core | CW617N | 1 | |
| 5 | | Flat nut | Brass | 1 | Nickel plating |
| 4 | | Stainless steel sleeve | SS304 | 2 | |
| 3 | | Male thread adapter | CW617N | 1 | Nickel plating |
| 2 | | Olive | H65 | 1 | |
| 1 | | Compersion Nut | Brass | 1 | Nickel plating |

| | | | |
|--|--------------|------------------------------|--|
| Title | | 22Cx3/4Fx90CM Flex Tap Con - | |
| WRAS | | | |
| Mark | Modification | Date | |
| Drawn: | | | |
| Checked: | | | |
| Appr.: | | | |
| Tolerances unless otherwise specified: ISO 2768-mk | | | |



| | | | | |
|-------------|---------------|------------|-------|-----------|
| NO.: | | Projection | Scale | Size |
| Material: | | | 1:1 | A4 |
| Weight | | | | |
| Client NO.: | MFLXCTC220690 | NO.: | | Sheet 1/1 |
| REV. | 01 | | | |