



CODE	Description	A	B	C	D	E
M69150000G	LEVER B/V YELLOW HANDLE 15MM (High Temp Approved)	15MM	14.5	70.5	47	88
M69220000G	LEVER B/V YELLOW HANDLE 22MM (High Temp Approved)	22MM	19	82	52	100
M69280000G	LEVER B/V YELLOW HANDLE 28MM (High Temp Approved)	28MM	24.5	91	65	125

Specification

Fields of applications: gas and water;

Maximum working pressure: 25bar(water); 5bar(gas)

Operating temperature range: -20 ~ +110°C(water); -20 ~ +60°C(gas) ;

Valves are manufactured in accordance with EN331;

Compression connections comply with EN1254-2;

WRAS approved, full bore.

12		Olive	2	H65	
11		ComperSSION nut	2	Brass	NP
10		Handle	1	Q235+PVC	Yellow
9		Nut	1	SS304	
8		Lock nut	1	Brass	NP
7		Stem	1	Brass	NP
6		Packing	1	PTFE	WRAS approve
5		O-ring	1	NBR	WRAS approve
4		Ball seat	2	PTFE	WRAS approve
3		Ball	1	CW617N	Chrome plated
2		Bonnet	1	CW617N	NP
1		Body	1	CW617N	NP
NO.	Parts NO.	parts name	QTY.	material	

			<i>Title</i>		Projection	Scale	Size
			Gas ball valve with lever handle WRAS approval			1:1	A4
					Material:	Weight	
					CW617N	×g	
Mrk	Modification	Date	IDC BEIJING			NO.:	Sheet
Drawn :	Alger.li					Client NO.:	1/1
Checked:							REV.
Appr.:							01
Tolerances unless otherwise specified: ISO 2768-mk							