



Batch number month/year

Specification
 Solid forged Brass
 Full Bore friendly leak detection feature
 M-Profile Press blow-out proof stem
 Performance Rating
 Maximum working pressure: 16 bar
 Maximum working temperature: 99°C
 Unique plastic wrap design helps to easily detect any joint that is not pressed

CODE	SIZE	A	L	H
MCP69150000	15MM	15	74	51
MCP69220000	22MM	22	86	54
MCP69280000	28MM	28	99	63.5
MCP69350000	35MM	35	113.5	69.5
MCP69420000	42MM	42	136	87
MCP69540000	54MM	54	164.5	93

NO.	Parts NO.	parts name	QTY.	material	
11		O-ring	2	EPDM	Leak detection O-ring
10		Nut	1	SS201	
9		Handle	2	Q235+PVC	
8		Lock Nut	1	Brass	
7		Packing	1	PTFE	
6		O-ring	2	EPDM	
5		Stem	1	Brass	
4		Bonnet	1	CW602N	
3		Ball	1	Brass	
2		Ball seat	2	PTFE	
1		Body	1	CW602N	

			Title		Projection	Scale	Size
			PrimaPress Pressfit Ball Valve			1:1	A4
					Material:		Weight
Mrk	Modification	Date					
Drawn :					NO. :		Sheet
Checked:					Client NO. :		1/1
Appr. :							REV.
Tolerances unless otherwise specified: ISO 2768-mk							01